

STOCKHOLM 288






















Type of luminaire	
Type of lumianire	Bollard.
Photometric body	Uncovered, diffused light with rotationally symmetrical light distribution.
Characteristics of the luminaire	Bollard luminaire of stable and durable construction. For lighting private areas and public spaces.

General information	
Materials	Hot-dip galvanized steel. Lens - plastic PMMA in milky color. Silicone gasket.
Mounting method	Fixing of the luminaire: 3 holes ø9mm with a diameter of ø56mm every 120 °.
Terminal	Connection terminals: max 3x2,5mm², possibility to connect luminaire in loop max 3x2,5mm². A round wire in the isolation with a diameter of max ø12,5mm.
Type of light source	E27 lamp Replaceable light source by an end-user.
Net / gross weight of luminaire	9,55kg / 10,85kg

Technical data		
E27 lamp	LED A5560	
Light source wattage	LED max 9W	
Ta Rated temperature	+25°C	

Accessories sold separately	
205ZX0010	Concreting anchor.
206GA0010	Ground anchor.
206GA0S10	Anchoring support.

Recommended light sources		
Osram LED Parathom Classic E27	Philips Master LEDbulb / Ledbulb Classic E27	
Osram ECO PRO Classic 46<=>60W E27	Philips ECO Classic 42<=>60W E27	

Spare parts	
06281004	Lens
08288002	Gasket.

Files to download	
Photometric LDT files	Photometric IES files
Manual	

Indexes		
Index	Color	RAL
288B	BLACK	9005
288GA	GALVANIZED	-





