




Stockholm 299XX0010
24.11.2022 v.10.5
www.norlys.com









Type of luminaire					
Type of lumianire	Bollard.				
Photometric body	Uncovered, diffuse	ed light with rotationally symmetrical light distribution.			
Characteristics of the luminaire	Bollard luminaire of stable and durable construction. For lighting private areas and public spaces.				
General information					
Materials	Hot-dip galvanized	l steel. Lens - plastic PMMA in milky color. Silicone gasket.			
Mounting method	Fixing of the lumin	aire: 3 holes ø9mm with a diameter of ø56mm every 120 °.			
Terminal	Connection termin diameter of max ø	als: max 3x2,5mm². A round wire in the isolation with a 12mm.			
Type of light source	E27 lamp Replaceable light s	source by an end-user.			
Net / gross weight of luminaire	4,45kg / 4,85kg				
Box dimensions [cm]	32x20x20				
Technical data					
E27 lamp	LED A5560				
Light source wattage	LED max 9W				
Ta Rated temperature	+25°C				
Accessories sold separately					
205ZX0010	Concreting anchor.				
206GA0010	Ground anchor.				
206GA0S10	Anchoring support.				
Recommended light sources					
Osram LED Parathom Classic E27		Philips Master LEDbulb / Ledbulb Classic E27			
Osram ECO PRO Classic 46<=>60W	/ E27	Philips ECO Classic 42<=>60W E27			
Spare parts					
06281004	Lens				

Ö≓Ö

Files to download

r nes to download			
Photometric LDT files	Photometric IES files		
Indexes			
Index	Color	RAL	
299B	BLACK	9005	
299GA	GALVANIZED	-	





